


article no.	ØD mm	Ød mm	Lo mm	m1 mm	m2 mm	Bemerkung / comment
PD 20-00	16,0	2,4	65	3,0	3,0	verzinkt / galvanized
PD 20-01						
PD 20-02						
PD 20-03	20,0	2,7	100	6,5	6,5	verzinkt, verstärkt / galvanized, reinforced, *
PD 20-04	22,0	2,5	125	5,5	5,5	verzinkt / galvanized
PD 20-05	20,0	2,7	130	6,5	6,5	verzinkt / galvanized
PD 20-06	20,0	2,8	130	6,5	6,5	verzinkt / galvanized, **
PD 20-07	20,0	3,0	130	6,5	6,5	verzinkt / galvanized
PD 20-08	20,0	2,0	150	6,5	6,5	verzinkt / galvanized
PD 20-09	20,0	2,7	155	6,5	6,5	verzinkt / galvanized
PD 20-10						
PD 20-11	20,0	2,7	205	6,5	6,5	verzinkt / galvanized
PD 20-12	20,0	3,0	205	8,5	8,5	verzinkt / galvanized
PD 20-13						
PD 20-14						
PD 20-15						
PD 20-16	9,0	1,1	33	0	4,0	verzinkt / galvanized
PD 20-17	8,0	1,3	32	3,0	3,0	roh / unfinished
PD 20-18	8,0	1,2	42	0	4,0	roh / unfinished
PD 20-19						
PD 20-20	9,0	1,1	33	0	0	phosphatiert, Deltaseal, PTFE
PD 20-21	12,3	2,2	130	3,5	3,5	verzinkt / galvanized
PD 20-22	9,5	1,0	40	3,0	3,0	verzinkt / galvanized
PD 20-23						
PD 20-24						

article Zugfeder tension spring				article-no. Index 004	
 Tel.: +49 521 9417-0 info@lusch.de				date/name 06.05.19/Bd	
name Tw		name <i>J.S.</i> <i>13</i>		PD 20-00 --> PD 20-24	
